

## DECLARATION OF PERFORMANCE

## according to Annex III of the regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

Nr. RE 820 U 230629

1. Unique identification code of the product-type:

KÖSTER ECB 2.0 U

2. Intended use:

Homogeneous plastic waterproofing membrane made of ethylene copolymer bitumen (ECB) according to DIN EN 13967:2012+A1:2017 Waterproofing membrane for building waterproofing against soil moisture and water.

3. Manufacturer:

KÖSTER BAUCHEMIE AG Dieselstraße 1 - 10 26607 Aurich

4. System of assessment and verification of constancy of performance:

System 2+

5a. Harmonized standard:

EN 13967:2012+A1:2017

5b. Notified body:

Materialprüfanstalt (MPA) für das Bauwesen,

Beethovenstraße 52 38106 Braunschweig Kennnummer 0761-CPD



## 6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	
Watertightness		
Method A	≥ 60 kPa Watertight (24h)	
Method B	≥ 400 kPa Watertight (72h)	
Tensile characteristics		
Tensile strength	≥ 9 N/mm²	
Elongation at break	≥ 700 %	
Resistance to static loading		
Method A	≥ 20 kg	
Method B	≥ 20 kg	
Resistance to shock loads		EN 13967:2012+A1:2017
Method A	≥ 800 mm	
Method B	≥ 1750 mm	
Tear continuation resistance	≥ 400 N	
Water vapor permeability	$\mu = 100.000$	
Resistance of the joint seams to	failure outside	
shearing	the joint seam	
Exposure to heat aging	Watertight	
Exposure to bitumen	Watertight	
Exposure to liquid chemicals including water	Watertight	

The performance of the product identified above in No. 1 and 3 is in conformity with the set of declared performance according to No. 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified above in No. 4.

Signed for and on behalf of the manufacturer by:

Dr. Thorsten Lauterbach (Research and Development Export)

Aurich, 29.06.2023

(Place and date of issue)

(signature)